



CERTIFICATE NUMBER
EFFECTIVE DATE
EXPIRY DATE
ABS TECHNICAL OFFICE

20-2010563-PDA
04-Aug-2020
03-Aug-2025
Gdynia Engineering Department

CERTIFICATE OF Product Design Assessment

This is to certify that a representative of this Bureau did, at the request of

WOUTER WITZEL EUROVALVE B.V.

located at

**INDUSTRIETERREIN DE POL 12, P.O. BOX 54, LOSSER,
Netherlands, 7581 CZ**

assess design plans and data for the below listed product. This assessment is a representation by the Bureau as to the degree of compliance the design exhibits with applicable sections of the Rules. This assessment does not waive unit certification or classification procedures required by ABS Rules for products to be installed in ABS classed vessels or facilities. This certificate, by itself, does not reflect that the product is Type Approved. The scope and limitations of this assessment are detailed on the pages attached to this certificate.

Product Valve, Butterfly

**Model EVS-i flangeless wafer type DN 400-600,
EVFS-i double flange DN 400-600,
EVTLS-i lugged wafer type DN 400-600.**

This Product Design Assessment (PDA) Certificate remains valid until 03/Aug/2025 or until the Rules and/or Standards used in the assessment are revised or until there is a design modification warranting design reassessment (whichever occurs first).

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or previous to the effective date of the ABS Rules and standards applied at the time of PDA issuance. Use of the Product for non-ABS units is subject to agreement between the manufacturer and intended client.

American Bureau Of Shipping

Tomasz Marszewski, Engineer/Consultant

NOTE: This certificate evidences compliance with one or more of the Rules, Guides, standards or other criteria of ABS or a statutory, industrial or manufacturer's standards. It is issued solely for the use of ABS, its committees, its clients or other authorized entities. Any significant changes to the aforementioned product without approval from ABS will result in this certificate becoming null and void. This certificate is governed by ABS Rules 1-1-A3/5.9 Terms and Conditions of the Request for Product Type Approval and Agreement (2010)

TERMS & CONDITIONS OF ABS DESIGN ASSESSMENT

1. AGREEMENT

Unless otherwise agreed in writing, all services rendered and certificates issued are governed by the terms and conditions of the "Request for Product Type Approval and Agreement" (the "Agreement") which are hereby incorporated by reference.

2. REPRESENTATIONS AS TO DESIGN ASSESSMENT

A certificate of design assessment represents that the product design meets the ABS, statutory, industrial or manufacturer's standard described on the reverse hereof and that the manufacturer has established a systematic quality monitoring system sufficient to show its capacity to consistently manufacture a product which meets the designated standards. ABS is not a substitute for the independent judgment of professional designers or engineers nor a substitute for the quality control procedures of constructors, steel makers, suppliers, manufacturers and vendors of marine structures, materials, machinery or equipment. ABS represents solely to the manufacturer or other client of ABS that it will use due diligence in developing Rules, Guides and standards and in surveying the plant as called for by ABS criteria for type approval.

3. SUSPENSION OF CERTIFICATION

Any of the following events will cause immediate suspension of the certificate of design assessment unless the change is submitted to ABS for a new review and audit.

- a) Redesign of the product or products covered by this certificate;
- b) Change in production methods;
- c) Substantial change in management organization;
- d) Substantial change in frequency or curriculum for personnel training;
- e) Refusing access to ABS personnel for periodic or annual audits;
- f) Failure to correct a non-compliance identified during an audit or in service;
- g) Failure to pay ABS fees.

4. VALIDITY

The validity, applicability and interpretation of a certificate issued under the terms of or in contemplation of ABS Type Approval are governed by the Rules, Guides and standards of American Bureau of Shipping which shall remain the sole judge thereof. Nothing contained in this certificate or in

any report issued in contemplation of this certificate shall be deemed to relieve any designer, builder, owner, manufacturer, seller, supplier, repairer, operator or other entity of any warranty express or implied, nor create any interest, right, claim or benefit in any third party. It is understood and agreed that nothing expressed herein is intended or shall be construed to give any person, firm or corporation other than the parties hereto, any right, remedy, or claim hereunder or under any of the provisions herein contained; all of the provisions hereof are for the sole and exclusive benefit of the parties hereto.

5. LIMITATION

ABS makes no representations beyond those contained herein and in the provisions of the Agreement regarding its reports, statements, plan review, surveys, certificates or other services.

6. HOLD HARMLESS

The party to whom this certificate is issued, and his assignee and successor in interest, agree to indemnify and hold harmless ABS from and against any and all claims, demands, lawsuits, or actions for damages, including legal fees, to persons or other legal entities and property, tangible, intangible, or otherwise which may be brought against ABS incidental to, arising out of or in connection with the work done, services performed or material to be furnished under this certificate, except for those claims caused solely and completely by the negligence of ABS, its agents, employees, officers, directors or subcontractors.

7. ARBITRATION

Any and all differences and disputes of whatsoever nature arising out of this agreement shall be put to arbitration in the City of New York pursuant to the laws relating to the arbitration there in force, before a board of three persons, consisting of one arbitrator to be appointed by ABS, one by Client, and one by the two so chosen. The decision of any two of the three on any point or points shall be final. Until such time as the arbitrators finally close the hearings either party shall have the right by written notice served on the arbitrators and on an officer of the other party to specify further disputes or difference under this Agreement for hearing and determination. The arbitration is to be conducted in accordance with the rules of the Society of Maritime Arbitrators, Inc. The arbitrators may grant any relief, other than punitive damages,

which they, or a majority of them, deem just and equitable and within the scope of the agreement of the parties, including, but not limited to, specific performance. Awards made in pursuance to this clause may include costs including a reasonable allowance for attorney's fees and judgment may be entered upon any award made hereunder in any court having jurisdiction. ABS and client hereby mutually waive any and all claims to punitive damages in any forum.

Client shall be required to notify ABS within thirty (30) days of the commencement of any arbitration between it and third parties which may concern ABS's work in connection with this Agreement and shall afford ABS an opportunity, at ABS's sole option, to participate in the arbitration.

8. TIME BAR TO LEGAL ACTION

Any statutes of limitation notwithstanding, Client expressly agrees for itself and its affiliated companies that its right to bring or to assert against ABS any and all claims, demands or proceedings whether in arbitration or otherwise shall be waived unless (a) notice is received by ABS within thirty (30) days after Client or its affiliates had notice of or should reasonably have been expected to have had notice of the basis for such claims; and (b) arbitration or legal proceedings, if any, based on such claims or demands of whatever nature are commenced within one (1) year of the date of such notice to ABS.

9. LIMITATION OF LIABILITY

The combined liability of American Bureau of Shipping, its officers, employees, agents or subcontractors for any loss, claim, or damage arising from negligent performance or non-performance of any services under this Agreement, of from breach of any implied or express warranty of workmanlike performance in connection with the services, or from any other reason, to any person, corporation, partnership, business entity, sovereign, country or nation, shall be limited to the greater of a) \$100,000 or b) an amount equal to ten times the sum actually paid for the services alleged to be deficient.

The limitation of liability may be increased up to an amount twenty-five times that sum paid for services upon receipt of Client's written request at or before the time of performance of service and upon payment by Client of an additional fee of \$10.00 for every \$1,000.00 increase in the limitation.

WOUTER WITZEL EUROVALVE B.V.

INDUSTRIETERREIN DE POL 12

P.O. BOX 54

LOSSER

Netherlands 7581 CZ

Telephone: +31 (0)53 536 95 36

Fax: + 31 53 536 95 00

Email: info@wouterwitzel.nl

Web: www.wouterwitzel.nl

Tier: 3 - Type Approved, unit certification not required

Product: Valve, Butterfly

Model: EVS-i flangeless wafer type DN 400-600,
EVFS-i double flange DN 400-600,
EVTLS-i lugged wafer type DN 400-600.

Intended Service:

For use in fresh water, seawater, sanitary, hydrocarbons (oils and gases), compressed air, steam, chemicals and solvents.

Description:

Body materials - Ductile iron, carbon steel and bronze.

Disc materials - Stainless steel, stainless steel duplex and NiAlBronze, Super Duplex.

Linings - NBR (Acrylonitrile Butadiene Rubber), EPDM (Ethylene Propylene DM) or FPM (Fluoroelastomer) lining.

Rating:

EVS-i: DN 400 ÷ 600, 10/16 bar

EVFS-i: DN 400 ÷ 600, 10/16 bar

EVTLS-i: DN400 ÷ 600, 10/16 bar

Temperature rating: -18 °C to 200 °C

Service Restriction:

1. Butterfly valves are not to be used as an isolation valves on main fire system.
2. Gray cast iron valves are not to be used for the following applications: (ABS Marine Vessels Rules (MVR) 4-6-2/3.1.4)
 - Temperature above 220 °C
 - Connected to the shell of the vessel
 - Connected to the collision bulkhead
 - Fitted on the outside of fuel oil, lubricating oil, hydraulic oil and cargo oil tanks were subjected to a static head of oil
 - Mounted on boilers
 - Cargo oil weather decks for pressure exceeding 16 bar.
 - Cargo oil manifolds for connection to cargo handling hoses.
 - Fixed gas fire extinguishing systems
4. Wafer type valves are not permitted to be used as shell valves (ABS MVR 4-6-2/9.13.2).
5. Materials rendered ineffective by heat are not to be used in shell valves.
6. Nodular iron may be used for Classes I and II piping systems and for valves listed in (4-6-2/3.1.4 of ABS MVR), provided it has an elongation of not less than 12% in 50 mm (2 in.). (4-6-2/3.1.5 of ABS MVR)
7. Wafer type butterfly valves are not to be installed next to rubber expansion joints with beaded end flange. (4-6-2/9.5 vi) of ABS MVR).
8. EPDM seated valves are not to be used for hydrocarbon services.
9. Butterfly valves are not to be used on the outside of oil tanks where subjected to a static head of oil.
10. Unit Certification is not required for these products. If the manufacturer or purchaser request ABS Certificate for compliance with a specification or standards, the specification or standard, including inspection standards and tolerances, must be clearly defined.

Comments:

1. The Manufacturer has provided a declaration about the control of, or the lack of Asbestos in this product.
2. This certificate may not be used for EU and US Flagged Vessels (MED and/or USCG have their own specific/requirements).
3. Butterfly valves intended for installation on ship-side shell, including valves at sea chests, are to be hydrostatic tested, before installation, to a pressure of at least 5 bar, in the presence of the Surveyor. (4-6-2/7.3.2 of ABS MVR)
4. Remote control valves are to be provided with a readily accessible manual means of operation upon loss of power.

WOUTER WITZEL EUROVALVE B.V.

INDUSTRIETERREIN DE POL 12

P.O. BOX 54

LOSSER

Netherlands 7581 CZ

Telephone: +31 (0)53 536 95 36

Fax: + 31 53 536 95 00

Email: info@wouterwitzel.nl

Web: www.wouterwitzel.nl

Tier: 3 - Type Approved, unit certification not required

(4-6-2/9.13.2 iv), 4-6-4/7.5.2 & 5C-1-7/3.5.1 of ABS MVR). If installed as side shell valve open or closed indicators are to be provided. (4-6-2/9.13.2 iii) of ABS MVR.

5. Wafer type valves with non-conductive gaskets seals are to be earthed (grounded) to the hull such that the resistance between any point on the piping and the hull (across joints, pipe to hull) does not exceed 1 mega-ohm. (4-6-2/9.15 of the ABS MVR)

6. Valves are to be of a type with positive holding arrangements, or equivalent that will prevent movement of the valve position due to vibration or flow of fluids. (4-6-4/7.5.1 of ABS MVR)

7. All valves are to bear permanent identification, such as manufacturer's name or trademark, standard of compliance, material identity, pressure rating, etc., as required by the standard of compliance or the manufacturer's specification. Such markings may be cast or forged integral with, stamped on, or securely affixed by nameplate on the component, and are to serve as a permanent means of identification of the component throughout its service life.

Notes/Drawing/Documentation:

PDS01 61 001 - Wouter Witzel - EVS-i, Product data sheet,

PDS01 62 001 - Wouter Witzel - EVFS-i, Product data sheet,

PDS01 63 001 - Wouter Witzel - EVTLS-i, Product data sheet,

GD102 01 01 001-B - Body EV-i - Double Flange_DN500_PN10 - FCC2001_2020-04-09, Calculation,

GD102 01 01 001-B - Body EV-i - Double Flange_DN500_PN16 - FCC2000_2020-04-09, Calculation,

GD102 01 01 001-B - Body EV-i - Double Flange_DN600_PN10 - FCC2402_2020-04-09, Calculation,

GD102 01 01 001-B - Body EV-i - Double Flange_DN600_PN16 - FCC2401_2020-04-09, Calculation,

GD102 01 01 001-B - Body EV-i - Wafer_DN400_PN16 - FCA1601_2020-04-09, Calculation,

GD102 01 01 001-B - Body EV-i - Wafer_DN450_PN16 - FCA1800_2020-04-09, Calculation,

GD102 01 01 001-B - Body EV-i - Wafer_DN500_PN16 - FCA2000_2020-04-09, Calculation,

GD102 01 01 001-B - Body EV-i - Wafer_DN600_PN16 - FCA2400_2020-04-09, Calculation.

Terms of Validity:

This Product Design Assessment (PDA) Certificate remains valid until 03/Aug/2025 or until the Rules and/or Standards used in the assessment are revised or until there is a design modification warranting design reassessment (whichever occurs first).

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or previous to the effective date of the ABS Rules and standards applied at the time of PDA issuance. Use of the Product for non-ABS units is subject to agreement between the manufacturer and intended client.

STANDARDS

ABS Rules:

Rules for Conditions of Classification, Part 1 - 2020 Marine Vessels Rules 1-1-4/7.7, 1-1-A3, 1-1-A4, which covers the following:

2020 Marine Vessels Rules 4-6-1/7, 4-6-2/3, 4-6-2/5.11, 4-6-2/9.13

Rules for Conditions of Classification, Part 1 - 2020 Offshore Units and Structures 1-1-4/9.7, 1-1-A2, 1-1-A3, which covers the following:

2020 Mobile Offshore Units Rules 4-2-2/9, 4-2-2/17, 4-2-2/21.3

National:

BS EN 593:2017 Industrial valves. Metallic butterfly valves for general purposes.

WOUTER WITZEL EUROVALVE B.V.

INDUSTRIETERREIN DE POL 12

P.O. BOX 54

LOSSER

Netherlands 7581 CZ

Telephone: +31 (0)53 536 95 36

Fax: + 31 53 536 95 00

Email: info@wouterwitzel.nl

Web: www.wouterwitzel.nl

Tier: 3 - Type Approved, unit certification not required

API 609:Eighth Edition, February 2016; Butterfly Valves: Double-flanged, Lug- and Wafer-type

International:

ISO 5208:2015; Industrial valves — Pressure testing of metallic valves.

ISO 5752:1982(en) Metal valves for use in flanged pipe systems — Face-to-face and centre-to-face dimensions.

Government:

NA

EUMED:

NA

OTHERS:

NA