



Product certificate K92888-7

Issued 2025-07-01

Replaces K92888/06

Page 1 of 4

Butterfly Valves

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Wouter Witzel EuroValve B.V.

as specified in this product certificate and marked with the Kiwa[®]-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K602 "Closing accessories for drinking water transport and drinking water distribution systems" dated 21-04-2023,

and as stated in the additional requirements

EN 1074-1:2000: " Valves for water supply - Fitness for purpose requirements and appropriate verification tests - Part 1: General requirements".

EN 1074-2: 2000: "Valves for water supply – Fitness for purpose requirements and appropriate verification tests – Part 2: Isolating valves".

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

CERTIFICATE

287180711

Kiwa Nederland B.V.

Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
NL.Kiwa.info@Kiwa.com
www.kiwa.nl

Company

Wouter Witzel EuroValve B.V.
De Pol 12
7581 CZ LOSSER
The Netherlands
Tel. +31 (0)53-5369536
Fax +31 (0)53-5369500
info@wouterwitzel.nl
www.wouterwitzel.nl



Certification process
consists of initial and
regular assessment of:

- quality system
- product

Butterfly Valves

PRODUCT SPECIFICATION

The products mentioned below belong to this product certificate

Centric, Rubber lined (bonded to the body) Butterfly Valves, types:

Durability: 2500 cycles

<p><u>EVS – Flangeless wafer type (short)</u> Operation: manually, pneumatically, electrically or hydraulically PN 6, PN 10 en PN 16 DN 50, DN 65, DN 80, DN 100, DN 125, DN 150, DN 200, DN 250, DN 300, DN 350, DN 400, DN 450, DN 500, DN 600, DN 700, DN 750, DN 800, DN 900, DN 1000, DN 1200, DN 1400.</p>	<p><u>EVMS – Central single flange type (short)</u> Operation: manually, pneumatically, electrically or hydraulically PN 6,PN 10 and PN 16 DN 350, DN 400, DN 450, DN 500, DN 600, DN 700, DN 800, DN 900, DN 1000.</p>
<p><u>EVL – Flangeless wafer type (long)</u> Operation: manually, pneumatically, electrically or hydraulically PN 6, PN 10 en PN 16 DN 50, DN 65, DN 80, DN 100, DN 125, DN 150, DN 200, DN 250, DN 300. .</p>	<p><u>EVFS - Double flanged type (short)</u> Operation: manually, pneumatically, electrically or hydraulically PN 6, PN 10 en PN 16 DN 50, DN 65, DN 80, DN 100, DN 125, DN 150, DN 200, DN 250, DN 300, DN 350, DN 400, DN 450, DN 500, DN 550, DN 600 DN 650, DN 700, DN 750, DN 800, DN 900, DN 1000, DN 1200, DN 1400, DN 1500, DN 1600, DN 1800, DN 2000.</p>
<p><u>EVBS - Semi lug wafer type (short)</u> Operation: manually, pneumatically, electrically or hydraulically PN 6, PN 10 en PN 16 DN 50, DN 65, DN 80, DN 100, DN 125, DN 150, DN 200, DN 250, DN 300</p>	<p><u>EVFL - Double flanged type (long)</u> Operation: manually, pneumatically, electrically or hydraulically PN 6, PN 10 en PN 16 DN 50, DN 65, DN 80, DN 100, DN 125, DN 150, DN 200, DN 250, DN 300, DN 350, DN 400, DN 450, DN 500, DN 600, DN 700, DN 800, DN 900, DN 1000, DN 1200, DN 1400, DN 1500.</p>
<p><u>EVTLS - Lugged wafer type with tapped holes (short)</u> Operation: manually, pneumatically, electrically or hydraulically PN 6, PN 10 en PN 16 DN 50, DN 65, DN 80, DN 100, DN 125, DN 150, DN 200, DN 250, DN 300, DN 350, DN 400, DN 450, DN 500, DN 600, DN 700, DN 750, DN 800, DN 900, DN 1000, DN 1200.</p>	<p><u>EVUS, "U"-section wafer type (short)</u> Operation: manually, pneumatically, electrically or hydraulically DN 700, DN 750, DN 800, DN 900, DN 1000, DN 1200, DN 1300, DN 1400, DN 1500, DN 1600, DN 1700, DN 1800, DN 2000, DN 2100, DN 2200.</p>
<p><u>EVML – Central single flange type (long)</u> Operation: manually, pneumatically, electrically or hydraulically PN 6, PN 10 en PN 16 DN 50, DN 65, DN 80, DN 100, DN 125, DN 150, DN 200, DN 250, DN 300, DN 350, DN 400, DN 500, DN 600, DN 700, DN 750, DN 800.</p>	<p><u>Type Euronomic, semi lug wafer type</u> Operation: manually. PN 6, PN 10 en PN 16 DN 50, DN 65, DN 80, DN 100, DN 125, DN 125, DN 150, DN 200, DN 250, DN 300.</p>

Butterfly Valves

Centric, Rubber lined (bonded to the body) Butterfly Valves, types:

Durability: 2500 cycles

<p>EVS-i Flangeless wafer type (short) Operation: manually, pneumatically, electrically or hydraulically Rating: PN6, PN 10 and PN 16</p> <p>DN 400, DN 450, DN 500, DN 550, DN 600, DN 650, DN 700, DN 750, DN 800, DN 900, DN 1000.</p>	<p>EVCS-i Semi lug wafer type (short) Operation: manually, pneumatically, electrically or hydraulically Rating: PN6, PN 10 and PN 16</p> <p>DN 40, DN 50, DN 65, DN 80, DN 100, DN 125, DN 150, DN 200, DN 250, DN 300, DN350.</p>
<p>EVCLS-i Semi lug wafer type (short) - long neck Operation: manually, pneumatically, electrically or hydraulically Rating: PN6, PN 10 and PN 16</p> <p>DN 40, DN 50, DN 65, DN 80, DN 100, DN 125, DN 150, DN 200, DN 250, DN 300.</p>	<p>EVTLS-i Lugged wafer type with tapped holes (short) Operation: manually, pneumatically, electrically or hydraulically Rating: PN6, PN 10 and PN 16</p> <p>DN 40, DN 50, DN 65, DN 80, DN 100, DN 125, DN 150, DN 200, DN 250, DN 300, DN 350, DN 400, DN 450, DN 500, DN 550, DN 600, DN 650, DN 700, DN 750, DN 800, DN 850, DN 900, DN 950, DN 1000, DN 1200.</p>
<p>EVMS-i Central single flange type (short) Operation: manually, pneumatically, electrically or hydraulically Rating: PN6, PN 10 and PN 16</p> <p>DN 50, DN 65, DN 80, DN 100, DN 125, DN 150, DN 200, DN 250, DN 300, DN 350, DN 400, DN 450, DN 550, DN 600, DN 650, DN 700, DN 750, DN 800, DN 850, DN 900, DN 950, DN1000, DN1100, DN 1200.</p>	<p>EVFS-i Double flanged type (short) Operation: manually, pneumatically, electrically or hydraulically Rating: PN6, PN 10 and PN 16</p> <p>DN 40, DN 50, DN 65, DN 80, DN 100, DN 125, DN 150, DN 200, DN 250, DN 300, DN 350, DN 400, DN 450, DN 550, DN 600, DN 650, DN 700, DN 750, DN 800, DN 900, DN1000, DN 1200, DN 1400, DN 1500, DN 1600, DN 1800, DN 2000.</p>
<p>EVFL-i Double flanged type (long) Operation: manually, pneumatically, electrically or hydraulically Rating: PN6, PN 10 and PN 16</p> <p>DN 40, DN 50, DN 65, DN 80, DN 100, DN 125, DN 150, DN 200, DN 250, DN 300, DN 350, DN 400, DN 450, DN 600, DN 700, DN 800, DN 900, DN1000, DN 1200, DN 1300, DN 1400, DN 1500, DN 1600.</p>	<p>EVUS-i "U"-section wafer type (short) Operation: manually, pneumatically, electrically or hydraulically Rating: PN6, PN 10 and PN 16</p> <p>DN 600, DN 700, DN 750, DN 800, DN 900, DN1000, DN 1050, DN 1100, DN 1200, DN 1300, DN 1400, DN 1500, DN 1600, DN 1700, DN 1800, DN 1900, DN 2000, DN 2100, DN 2200.</p>

Butterfly Valves

Fitness for contact with drinking water

This product is approved on the basis of the requirements for hygienic aspects set in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Materials and chemicals in the supply of drinking water and warm tap water Regulation" dated 01-07-2017; published in the Government Gazette).

These hygienic aspects are based on two main criteria. The product shall permanently comply with:

- The product recipe approved during the assessment procedure. This recipe is not to be changed without prior approval by Kiwa according to the Kiwa approval procedure for the hygienic aspects;
- Specific product requirements for the hygienic aspects.

The recipe and specific product requirements are laid down in the for confidentiality reasons undisclosed 'appendix hygienic aspects' to this certificate.

MARKING

The Kiwa®-mark products are marked with the word mark "KIWA 

Place of the mark: - on the body or specification plate.

Compulsory specifications:

- name or mark of manufacturer: on the body or specification plate;
- identification of the shell material(s): on the body or specification plate;
- nominal size "DN ...": on the body or specification plate;
- nominal working pressure "PN ...": on the body or specification plate;
- identification of the year of manufacture: on the body or specification plate;
- number of the relevant part of the EN1074: on the body or specification plate.

•

Method of marking:

- Non-erasable;
- visible after assembly.

APPLICATION AND USE

Butterfly valves are designed to, both underground as above ground, be used in pipes for drinking water or raw material for drinking water, with a maximum medium temperature of 30 °C. The valves are designed to open or shut off the pipes and not for regulation purposes.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Wouter Witzel EuroValve B.V.

and, if necessary,

- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.